

REGAL PRO-MAX 4G

2,400 Watt SWITCHING CAPACITY for Aircraft Pre-Heaters!



High Power Pre-heaters manufactured by AEROTHERM and others are no problem for the **REGAL PRO-MAX 4G**, an interactive, remote switch with a 2.4 KW / 2 HP load capacity. High switching power, plus ease of use make **PRO-MAX** unique. Check out the features, specs, Performance and Support that back this extraordinary product.

FEATURES

- Outlet 1 has a 2400 Watt resistive capacity or a 2HP inductive capacity making PRO-MAX 4G suitable for aviation and non-aviation applications. Outlet 2 has a Maximum switching capacity of 1400 Watt resistive load.
- The outlets accept NEMA 5-15 and 5-20 plugs.
- Remote operations use the proven REGAL PRO control system. A free, user friendly, iPhone app is available or the unit can be controlled by any text capable cell phone.
- The outlets can be turned ON and OFF by App or text message. It can also be turned on for selected ON periods by App or text. Commands can be automatically confirmed or users can interrogate the unit.
- The unit can be programmed to turn on at a specific time in the next 24 hours and stay ON for a user selected time period. Activation and shut off are confirmed by text message or interrogation.
- A resident Program can be setup to turn the outlet ON for a user selected ON period when the unit's phone number is called. Only authorized phone numbers can activate the program.
- Power failures and restorations are both confirmed by text message.
- New Master Power LED indicator.

- Security provided by password and authorized user list. Unit is delivered with an active phone number and at least 75 days of cell service. PRO-MAX is ready to use out of the box.
- Cell Service is provided by a Pay-as-You-Go account on the ATT system. Costs of less than \$4.00 per month by user self-management are possible. A No-hassle annual subscription service, managed by FST LLC, is available for \$80.00 per year.

SPECIFICATIONS

- 120 VAC @ 50 or 60 Hz
- 20 Amp Capacity
- Protection: System protected by 20 A Circuit Breaker. Outlet 2 has 12 A fuse
- Power Entry, hard wired 12 AWG
- Temperature Range: -10° to 120° F
- Weight: 5.0 lbs
- Dimensions: Height 5.4 in, Width 6.0 in, Length 10.0 in.
- General Construction: All Aluminum enclosure, Gloss black paint, Carrying handle and non-marring feet, Medical grade DC power supply. Power Connections crimped and soldered.

WARRANTY: 12 months from shipping date (Cell service is not warranted)